



# VINPOL™ LD07018

## Low Density Polyethylene

Melt Index: 7.0

Density: 0.918

**VINPOL LD07018** is a general purpose LDPE extrusion coating grade designed for high speed coating in flexible packaging applications including laminating and aseptic packaging with paper, foil, cellophane, polyester film and other base stocks. This product has excellent adhesion, heat seal and low neck-in performance. This product meets requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520 and 21 CFR 176.170, covering safe use of polyolefin articles intended for direct food contact.

Resin Property	Typical Value	Units	Test Method
Melt Index, 2.16 Kg at 190 °C	7.0	g/10 min	ASTM D-1238
Density	0.918	g/cm <sup>3</sup>	ASTM D-1505
Tensile Strength	1,700	psi	ASTM D-638
Elongation Type IV speciman	550	%	ASTM D-638
Flexural Stiffness	30000	psi	ASTM D-790
Vicat Softening Point	84	°C	ASTM D-1525
Hardness	50	Shore D	ASTM D-2240
Moisture Vapor Transmission Rate	.26	g/m <sup>2</sup> , 24 hrs	ASTM E-96

Vinmar Polymers America cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties, but they should not be used to establish specification limits or used alone as the basis of design.