



VINPOL™ PC07U

Injection Molding Grade Polycarbonate

Melt Flow: 7.0

UV Stabilized

VINPOL PC070U Low flow polycarbonate resin with UV stabilizer (for outdoor and lighting applications) and UL HB flame rated. This product is designed for thicker molded sections without sinks.

Resin Property	Typical Value	Units	Test Method
Melt Flow, 1.2kgf @ 300°C	7.0	g/10 min	ASTM D-1238
Specific Gravity	1.2	-	ASTM D-792
Mold Shrinkage, flow, 3.2mm	0.5-0.7	%	Supplier Method
Water Absorption, 23°C/equilibrium	0.35	%	ASTM D-570
Water Absorption, 100°C/equilibrium	0.58	%	ASTM D-570
Water Absorption, 24 hours	0.15	%	ASTM D-570
Tensile Stress, yld, Type I, 50 mm/min	62	MPa	ASTM D-638
Tensile Stress, brk, Type I, 50 mm/min	65	MPa	ASTM D-638
Tensile Strain, yld, Type I, 50 mm/min	7	%	ASTM D-638
Tensile Strain, brk, Type I, 50 mm/min	110	%	ASTM D-638
Flexural Stress, yld, 1.3 mm/min, 50 mm span	93	MPa	ASTM D-790
Flexural Modulus, 1.3 mm/min, 50 mm span	2,340	MPa	ASTM D-790
Izod Impact, unnotched, 23°C	3,204	J/m	ASTM D-4812
Izod Impact, notched, 23°C	907	J/m	ASTM D-256
Vicat Softening Temp, Rate B/50	154	°C	ASTM D-1525
HDT, 0.45 MPa, 6.4 mm, unannealed	137	°C	ASTM D-648
HDT, 1.82 MPa, 6.4 mm, unannealed	132	°C	ASTM D-648
CTE, -40°C to 95°C, flow	6.84E-05	1/°C	ASTM E-831
UL Yellow Card, 94HB Flame Class Rating	0.73	mm	UL 94
Light Transmission, 2.54mm	88	%	ASTM D-1003
Haze, 2.54mm	1	%	ASTM D-1003
Refractive Index	1.586	-	ASTM D-542
Volume Resistivity	>1E+17	Ohm-cm	ASTM D-257

Vinmar Polymers America cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties, but they should not be used to establish specification limits or used alone as the basis of design.