



VINPOL™ PI800NS

Impact Copolymer Polypropylene

Melt Flow: 80

Density: 0.90

VINPOL PI800NS is an impact copolymer polypropylene designed for thin-wall injection molding applications requiring high flow and excellent low temperature impact resistance. Targeted applications include consumer products and rigid packaging, such as housewares, sports equipment, leisure and toy parts and TWIM food containers. This product contains anti-stat and nucleating additives.

Resin Property	Typical Value	Units	Test Method
Melt Flow	80	g/10 min	ASTM D-1238
Density	0.90	g/cm ³	ASTM D-792
Tensile Strength at Yield, 2 in/min (50 mm/min)	3,100 (21)	psi (MPa)	ASTM D-638
Tensile Elongation at Yield	5	%	ASTM D-638
Flexural Modulus, 1% Secant, 0.05 in/min (1.3 mm/min), Procedure A	155,000 (1,070)	psi (MPa)	ASTM D-790
Notched Izod Impact Strength, 73° F (23°C)	2.2 (117)	ft-lbf/in (J/m)	ASTM D-256A
Deflection Temp. Under Load (DTUL), 66psi (455kPa)	212 (100)	°F (°C)	ASTM D-648

Vinmar Polymers America cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties, but they should not be used to establish specification limits or used alone as the basis of design.