



VINPOL™ PTFL

Polyethylene Terephthalate Flake

VINPOL PTFL is a polyethylene terephthalate in flake/shredded form.

Resin Property	Typical Value	Units	Test Method
Flake Size	11	mm	Supplier Method
Bulk Density	18-20	lb/ft ³	Supplier Method
Moisture Content	≤ 1	%	Supplier Method
PVC	≤ 20	ppm	Supplier Method
Metal (Ferrous/Non-ferrous)	≤ 50	ppm	Supplier Method
Low Melt (PET-G/PS)	≤	ppm	Supplier Method
Caps-Floatables (PP, PE)	≤ 50	ppm	Supplier Method
Labels-Floatables	≤ 50	ppm	Supplier Method
Shrink Labels	≤ 50	ppm	Supplier Method
Hard Solids	≤ 50	ppm	Supplier Method
PET with Glue	0	ppm	Supplier Method
Light Blue	≤ 5-7	%	Supplier Method
Other PET Colors (include Green)	≤ 450	ppm	Supplier Method
Other Contaminants	≤ 50	ppm	Supplier Method
Fines < 0.5 mm	≤ 0.5	%	Supplier Method
Flakes with Glue	≤ 4000	ppm	Supplier Method
Yellowish Flake (Barrier)	≤ 4000	ppm	Supplier Method

Vinmar Polymers America cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties, but they should not be used to establish specification limits or used alone as the basis of design.